



LED FLOOD FIXTURE



15W, 30W & 50W
Knuckle Mount



30W & 50W
Yoke Mount



100W & 150W
Mount Sold Separately

PRODUCT FEATURES

- ADC12 Aluminum Heat Sink Housing
- Outdoor Powder Coating
- Bronze Finish
- IP65 Rating - Suitable for Wet Locations
- 100-277 Voltage Rating
- 50,000 Hour Lifetime Rating
- UL Certified
- 5-Year Limited Warranty
- High Light Transmittance PC, Anti-UV and Fire Resistance Lens
- Highly Conductive, Waterproof, Aging Resistance, Salt Mist Resistance Aluminum LED Board
- Operating Temperature: -40°F to 104°F (-40°C to 40°C)
- Mounts sold separately for 100W & 150W Flood Lamps
 - Slip-Fitter - CLF4-SLIP-100/150 (9.35 x 2.36 x 2.95)
 - Straight Arm - CLF4-STRAIGHT-100/150 (7.14 x 6.73 x 3.54)
 - Trunnion - CLF4-TRUN-100/150 (5.71 x 6.57 x 1.97)

PRODUCT SPECIFICATIONS

| MODEL | POWER (W) | LUMENS (LM) | CCT (K) | DIMENSIONS (IN) | EFFICIENCY (lm/W) | BEAM ANGLE / OPTIC TYPE | INCLUDED MOUNT |
|----------------|-----------|-------------|---------|----------------------|-------------------|-------------------------|----------------|
| CLF4-15P5YYZZ | 15 | 1800 | 5000 | 6.38 x 4.38 x 1.75 | 120 | 90° x 120° | KNUCKLE |
| CLF4-305YYZZ | 30 | 3450 | 5000 | 6.89 x 4.76 x 3.07 | 115 | 90° x 120° | KNUCKLE |
| CLF4-305YYZZ | 30 | 3450 | 5000 | 6.89 x 4.76 x 3.07 | 115 | 90° x 120° | YOKE |
| CLF4-505YYZZ | 50 | 6000 | 5000 | 8.62 x 5.94 x 3.54 | 120 | 90° x 120° | KNUCKLE |
| CLF4-50P5YYZZ | 50 | 6500 | 5000 | 9.38 x 9.75 x 2.00 | 130 | 90° x 120° | YOKE |
| CLF4-100P5YYZZ | 100 | 13,500 | 5000 | 11.00 x 12.58 x 3.38 | 135 | TYPE III | - |
| CLF4-150P5YYZZ | 150 | 20,250 | 5000 | 11.00 x 12.58 x 3.38 | 135 | TYPE III | - |

Note - "YY" Denotes Mount (If included). Can be KN=KNUCKLE or YK=YOKE.
 "ZZ" Denotes Housing Color. Can be BK=BLACK, BR=BRONZE or WH=WHITE.

